Material Safety Data Sheet

Date:	March 14,2019	
Name of Product:	KOPPER KARE, KOPPERSOL	
Product Information:	Topical Liquid	
Product Code:	10L-KKARE, 01L-KOPPE	
D.I.N.:	00603481 (Drug Identification Number)	
Manufacturer/Supplier:	Dominion Veterinary Laboratories Ltd. 1199 Sanford Street Winnipeg, Manitoba R3E 3A1 Telephone: (204) 586-3484 Fax: (204) 943-9612	

Product Identification

Product Use: Kopper Kare is used in the treatment of foot rot on cattle and sheep; thrush, hoof punctures and cracked hooves in horses; ringworm; wounds; after dehorning; as a pad toughener in dogs; and also for spongy hooves. It is a fungicide-antiseptic-astringent liquid.

Chemical Identity: Blend

CAS No. and Name:

Mineral Spirits: 8052-41-3 8% Copper Naphthenate: 1338-02-9

Formula and M. Wt.: Blend

Regulatory Section

WHMIS Classification:

8% Copper Naphthenate: Flammable Liquid, Class 3 Mineral Spirits: Flammable Liquid, Class 2

TDG Classification:

Flammable Liquid, n.o.s. (Petroleum Distillates) Class 3 UN 1993 Packing Group III

MSDS Kopper Kare Page 1 of 5

Hazardous Ingredients of Material

Hazardous Ingredients:				
Mineral Spirits: Light Distillate, Trimethyl Benzene 8% Copper Naphthenate				
Chemical Identity	CAS#/NA#/UN#	Conc. (w/w)	LD50	
8% Copper Naphthenate Mineral Spirits	13380206 / 1306 80454135	70-90% N/A	5050 mg/kg (oral rat) 5000 mg/kg (oral rat)	
	Physical / P	roperties Data		
Physical State: Partially slur	ried liquid.			
Appearance and Odour: Da	rk green liquid; paint like o	odour.		
Odour Threshold: 8% Copper Naphthenate: N/A Mineral Spirits: N/A		Boiling Pt. (Deg. C): N/A		
Specific Gravity: 0.872		Freezing Pt. (Deg. C): N/A		
Vapour Pressure: N/A		pH: N/A		
Evaporation Rate: N/A		Water Solubility: Not soluble in water		
	Reacti	vity Data		
Chemical Stability: N/A				
Incompatible Substances: S	trong oxidizing agent			
Conditions of Reactivity: N	/A			
Hazardous Decomposition P	roducts: N/A			

Fire or Explosion Hazards

Conditions of Flammability: Flammable with source of ignition.

Means of Extinction:

Large Fires: Use an all purpose type AFFF foam according to foam manufacturer's recommended techniques. The foam supplier should be consulted for recommendation regarding foam types and delivery rates for specific applications.

Small Fires: Use carbon dioxide or dry chemical media.

Flash Point and Method of Determination: (Deg. C) 52 Deg. C (Pensky-Martens)

Upper Flammable Limit: N/A

Lower Flammable Limit: N/A

Auto-Ignition Temperature: N/A

Hazardous Combustion Products:

Carbon Monoxide, Carbon Dioxide and Smoke Light Distillate, Trimethyl Benzene

Explosion Data - Sensitivity to Mechanical Impact: Stable

Explosion Data - Sensitivity to Static Discharge: Material will accumulate static charge which may cause an incendiary electrical discharge.

Effects of Acute Exposure

Route of Entry:

Skin Contact: Minimal absorption.

Eye Absorption: Slightly irritating but should not injure eye tissue.

Inhalation: Prolong or repeated exposure to high vapor concentrations may cause headache, nausea and/or dizziness.

Ingestion: High toxicity.

Effects of Chronic Exposure: Prolong or repeated exposure to high vapor concentration may cause headache, nausea and/or dizziness.

Toxicological and Health Data

Exposure Limits: N/A

Irritancy of Product: Prolong or frequent contact my irritate the skin and cause dermatitis.

Skin:

Eye: Slight irritating but should not injure eye tissue.

Sensitization to Material: N/A

Carcinogenicity: N/A

Reproductive Toxicity: N/A

Teratogenicity: N/A

Mutagenicity: N/A

Toxicological Synergistic Products: N/A

Preventive Measures

Personal Protective Equipment: Safety glasses, impermeable rubber gloves, synthetic apron, respirator or a half mask air purifying cartridge respirator.

Engineering Controls: Local mechanical exhaust ventilation capable of maintaining emissions at the point of use below the lowest pel.

Handling Procedures and Equipment: Avoid heat, sparks, and open flames.

Storage Requirements: Store in a cool, dry, well ventilated place away from incompatible materials, vent container frequently and more often in warm weather to relieve pressure. Protect material from direct electrical spark (ignition source).

Special Shipping Information: No special shipping requirements.

First Aid Measures

Skin Contact: Wash with soap and a large amount water. Removed severely contaminated clothing (including shoes) and launder before use.

Eye Contact: Flush eyes with large amount of water for 15 minutes. If irritation persists, get medical attention.

Inhalation: Remove to fresh air, restore breathing if required.

Ingestion: If swallowed, see a physician immediately.

Environmental Protection Data

Procedures for Handling Leaks or Spills: Eliminate source of ignition. Keep public away. Prevent additional discharge of material, if possible to do so without hazard. Prevent spills from entering sewers, water courses, or low areas. Contain spilled liquid with sand or earth, soak up with natural or synthetic absorbent. Do not use combustible materials such as saw dust. Recover by pumping (use an explosion proof motor or hand pump) or by using a suitable absorbent.

For Water Spillage: Remove from surface by skimming or with suitable absorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in unconfined water.

Waste Disposal: Dispose of by licensed and recognized operator.

Prepared by: D. Earn

Date: March 14, 2019

Checked by: _____D Earn_____

The information contained herein is, to the best of our knowledge, true and accurate. Any recommendations or suggestions are made without obligation on our part and the Company accepts no liability to any customers, their employees or any other person whatsoever for any loss, injury or damage whether direct or consequential, which may be caused by an error or emission from this sheet even if negligence or otherwise.

f:\user\lab\msds\kopper.doc

MSDS Kopper Kare Page 5 of 5