







Specifies this Thread size

Detach

# TOPAZ COMPACT VALVE

# PRODUCT INFO








**Topaz compact float valves** are float operated valves for use in the automatic filling of water troughs, tanks & cisterns where space is limited. The valve is configured for above water mounting only. The compact weighted float operates a small pilot valve which in turn operates the main diaphragm valve. Topaz Compact float valves are positive on/off and are ideal when working with pump supplied water in a small compartment.

### **Applications**

Maintaining Water Levels in:

- Animal Drinking Troughs
- Water Storage Tanks
- · Water Cisterns
- · Air Conditioning Systems
- High Pressure Cleaning Systems
- · Irrigation Applications

### Flow Graph



Flow Litres/Minute

Key


15mm (½")

20mm (¾") 25mm & 32mm (1" & 1 ¼")

#### Features

- · Compact Weighted Float
- High flow
- Compact robust construction
- Made from corrosion resistant materials
- Shuts down slowly to minimise water hammer
- 20 60mm (34" 2 ½") water level differential (increases as water inlet pressure increases)
- Pressure rating 0.3 10 Bar (5 - 150 PSI)
- Float position easily adjustable with no tools
- Valve has switch to lock it in off position
- Has port to connect Frostpro anti freeze device
- Detach™ Valve Seal Access System for quick access to valve seal

## Mounting Positions



to avoid back siphoning

N.B

N.B. Some mounting positions may not comply with local regulations

| Detach Base Short Tail  Detach Base C C C C C C C C C C C C C C C C C C C | (Options                  |          |          |          |          |          |          |          |          |  |  |  |
|---|---------------------------|----------|----------|----------|----------|----------|----------|----------|----------|--|--|--|
| Detach Base Short Tail  Detach Base C C C C C C C C C C C C C C C C C C C |                           | BSP      |          |          |          | NPT      |          |          |          |  |  |  |
| Short Tail  Detach Base   | Inlet Size                | 1/2"     | 3/4"     | 1"       | 1 1⁄4″   | 1/2"     | 3/4"     | 1"       | 1 1⁄4″   |  |  |  |
|   | Detach Base<br>Short Tail |          | <b>\</b> | <b>√</b> | <b>✓</b> |          | <b>\</b> | <b>\</b> | <b>✓</b> |  |  |  |
|   | Detach Base<br>Long Tail  | <b>✓</b> | ✓        | <b>✓</b> | ✓        | <b>✓</b> | ✓        | ✓        | <b>✓</b> |  |  |  |

Long Tail: Supplied with backnut and seal washer.

Floats: 55mm wide float supplied standard.

N.B. (No other float is compatible with this valve)

Compact Float



55mm

### **TOPAZ TROUGH VALVE SPECIFICATION**

| PRODUCT       | CODE | INLET SIZE  | CODE | OPTIONS          | CODE |
|---------------|------|-------------|------|------------------|------|
| Topaz Compact | TPVC | ½" bsp/npt  | 15   | Detach Base      | D    |
| Float Valve   |      | 34" bsp/npt | 20   | Long Tail Thread | LT   |
|               |      | 1" bsp      | 25   |                  |      |
|               |      | 1" npt      | 1    |                  |      |
|               |      | 1 ¼" bsp    | 32   |                  |      |
|               |      | 1 ¼" npt    | 114  |                  |      |

NOTE: If no options are specified the standard ones will be supplied

Note: Product may differ slightly from these specs due to ongoing product development.